


## MPRO 2500 THERMOSTATIC VALVE TRIM WITH INTEGRATED VOLUME CONTROL/THREE-WAY DIVERTER

Polished Chrome

US-PRO2500RC

### FEATURES

- MPRO combines iconic definition with versatile style and superb functionality
- Single integrated volume control/diverter for 3 water outlets
- Required rough features Vernet thermostatic cartridge
- The thermostatic valve senses and controls the actual water temperature and blends hot water with cold water to ensure constant, safe temperatures, preventing scalding.
- Required rough (sold separately): US-WLBP2500R




### SPECIFICATIONS

Finish	Polished Chrome
Extension kit	US-EK101525C
Barcode	5055806087880
Number of water outlets	3
Handle style	Lever
Flow rate	12 GPM
Inlet connection size	3/4" NPT
Outlet connection size	3/4" NPT
Water pressure minimum	20 PSI
Water pressure maximum	Operating pressure of 60 PSI and static pressure of 144 PSI
Installation type	Concealed

✔ Limited lifetime. Commercial

### AVAILABLE COLOR/FINISHES

Color	SKU	Description
	US-PRO2500RC	Polished Chrome
	US-PRO2500RV	Satin Nickel
	US-PRO2500RMB	Matte Black
	US-PRO2500RBB	Brushed Brass

MPRO 1000/1500/2500 Thermostatic Valve Trim

US-PRO1000

US-PRO1500

US-PRO2500

