

WISP 3000 THERMOSTATIC VALVE TRIM WITH INTEGRATED VOLUME CONTROL AND VOLUME CONTROL/TWO-WAY DIVERTER

Polished Chrome

US-WP3000RC

FEATURES

- Wisp defines contemporary design with simple elegance
- Integrated volume control and volume control/diverter for 3 water outlets
- Required rough features Vernet thermostatic cartridge
- The thermostatic valve senses and controls the actual water temperature and blends hot water with cold water to ensure constant, safe temperatures, preventing scalding.
- Required rough (sold separately): US-WLBP3000R



SPECIFICATIONS

Finish	Polished Chrome
Extension kit	US-EK2000C
Barcode	5055806087699
Number of water outlets	3
Handle style	Lever
Flow rate	12 GPM
Inlet connection size	3/4" NPT
Outlet connection size	3/4" NPT
Water pressure minimum	20 PSI
Water pressure maximum	Operating pressure of 60 PSI and static pressure of 144 PSI
Installation type	Concealed
IAPMO	Yes
State of MA	Yes

✓ Limited lifetime. Commercial



AVAILABLE COLOR/FINISHES

Color	SKU	Description
	US-WP3000RC	Polished Chrome
	US-WP3000RV	Satin Nickel

Wisp 2000/3000 Thermostatic Valve Trim

US-WP2000

US-WP3000

