

DUAL-CONTROL 3/4" THERMOSTATIC VALVE ROUGH WITH VOLUME CONTROL AND DIVERTER

Dual-control 3/4" Thermostatic Valve with Volume Control and Diverter Rough

TH2-RGH

FEATURES

- Solid brass construction
- Single integrated volume control/diverter for 2 water outlets
- Vernet thermostatic cartridge
- The thermostatic valve senses and controls the actual water temperature and blends hot water with cold water to ensure constant, safe temperatures, preventing scalding.



SPECIFICATIONS

| | |
|-------------------------|------------------------------------------------------------------------------------------------------------|
| Barcode | 5055806073999 |
| Number of water outlets | 2 |
| Flow rate | 10-12 GPM |
| Inlet connection size | 3/4" NPT |
| Outlet connection size | 3/4" NPT |
| Extension kit | 9Q242000CP - Polished Chrome 9Q242000RN - Polished Nickel 9Q242000AP - Satin Nickel 9Q242000FO - Bronze |
| Installation type | Concealed |
| Rough-in depth maximum | 3-1/4" |
| Rough-in depth minimum | 2-3/4" |
| IAPMO | Yes |
| State of MA | Yes |

✓ Limited lifetime. Commercial



Thermostatic Valve Rough

TH2-RGH

